

ACCESSORIES





Data Specification 2018 1300 071 378

Description

Connected Switchgear's active and neutral links are manufactured from a high percentage of brass material. Rated at 500V AC in both 110amp and 350amp. Accepts cable size up to 16mm² with up to 14 terminal holes. All links come with a cover indicating amperage and cable size to comply with Australian Wiring Rules.

Features

- Active links in red
- Neutral links in black
- •350amp links supplied with allen key



Approvals

Technical Parameters

Rated Voltage: 500V acRated Frequency: 50/60Hz

Complies with AS/NZS3000 Wiring Rules

ACESSORIES

Specifications

Product Code	Туре	Rating (Amps)	No. Of Terminals	Max Cable Sizes	Terminal Sizes
LA5	Active	110A	5	16mm²	1 x 4mm, 4 x 6mm
LA7	Active	110A	7	16mm²	4 x 6mm, 3 x 5mm
LA7-350	Active	350A	7	120mm²	2 x 8mm, 2 x 10mm, 1 x 5mm, 2 x 15mm
LA8	Active	110A	8	25mm²	8 x 7mm
LA10	Active	110A	10	25mm²	6 x 5mm, 4 x 7mm
LA12	Active	110A	12	25mm²	4 x 6mm, 8 x 4mm
LA13-350	Active	350A	13	120mm²	2 x 4mm, 8 x 5mm, 1 x 8mm, 2 x 15mm
LA14	Active	110A	14	25mm²	4 x 7mm, 10 x 5mm
LN5	Neutral	110A	5	16mm²	1 x 4mm, 4 x 6mm
LN7	Neutral	110A	7	16mm²	4 x 6mm, 3 x 5mm
LN7-350	Neutral	350A	7	120mm²	2 x 8mm, 2 x 10mm, 1 x 5mm, 2 x 15mm
LN8	Neutral	110A	8	25mm²	8 x 7mm
LN10	Neutral	110A	10	25mm²	6 x 5mm, 4 x 7mm
LN12	Neutral	110A	12	25mm²	4 x 6mm, 8 x 4mm
LN13-350	Neutral	350A	13	120mm²	2 x 4mm, 8 x 5mm, 1 x 8mm, 2 x 15mm
LN14	Neutral	110A	14	25mm²	4 x 7mm, 10 x 5mm

