











### [ DESCRIPTION ]

### SOLAR RATED ENCLOSURES

Connected Switchgears' range of solar rated enclosures are manufactured from impact and chemical resistant polycarbonate material to achieve an IP66 rating. The hinged transparent cover is lockable and comes complete with a 35mm din rail and a brass neutral link.

### [FEATURES]

- · Impact and Chemical Resistant
- Hose Proof and Dust Resistant Flaps
- Lockable Semi Transparent Door
- 35mm Din Rail
- Neutral Links Included
- Ample Conduit Entries

### [TECHNICAL PARAMETERS]

- IP Protection: IP66
- UV Stable and Flame Retardant ABS Bases
- Polycarbonate Covers
- Solar Rated
- 110amp Neutral Links

### [ COMPLIANCE ]

AS/NZS 61439.1:2016

### [IMAGES]



DBWC12S



DBWC12S Back



DBWC12S Front



DBWC12S Bottom

### [SPECIFICATIONS]

Product Code	Pole	Dimensions HxWxD	No. of Neutral Links	Conduit Entries	IP Rating
DBWC4S	4	200 x 120 x 100	1 x 5 Hole	4 x 25mm	IP66
DBWC6S	6	195 x 165 x 100	2 x 5 Hole	4 x 32mm	IP66
DBWC9S	9	195 x 220 x 100	2 x 7 Hole	4 x 32mm	IP66
DBWC12S	12	220 x 270 x 110	2 x 9 Hole	6 x 32mm, 4 x 22mm	IP66
DBWC18S	18	225 x 375 x 110	2 x 15 Hole	8 x 32mm, 4 x 22mm	IP66
DBWC24S	24	375 x 270 x 110	4 x 9 Hole	6 x 32mm, 4 x 22mm	IP66
DBWC36S	36	380 x 375 x 110	4 x 15 Hole	8 x 32mm, 4 x 22mm	IP66

### [WARRANTY]

Connected Switchgear weatherproof enclosures come with a trusted 5 Year In House Warranty. That means that you have peace of mind knowing that if a fault develops within a five year period, Connected Group Australia will cover the cost of replacing the product and it's installation.\*

\* See our website for full terms and conditions www.connectedswitchgear.com.au

### [ DESCRIPTION ]

### **IP65 TRADE ENCLOSURES**

Connected Switchgears' range of weatherproof IP65 rated enclosures are manufactured from dust and water resistant polycarbonate material to achieve an IP65 rating. The hinged transparent cover is lockable and comes complete with a 35mm DIN Rail.

#### [FEATURES]

- IP65 Rating
- UV Stable & Flame Retardant ABS
- Dust & Water Resistant
- Lockable Semi Transparent Door
- 35mm DIN Rail
- Neutral Links Included
- Security Cable Wire Hole
- Rubber Conduit Caps
- Ample Conduit Entries

### [ TECHNICAL PARAMETERS ]

- IP Protection: IP65
- 110amp Neutral Links
- UV Stable and Flame Retardant ABS Bases
- Polycarbonate Covers

[ COMPLIANCE ] AS/NZS 61439.1:2016

### [IMAGES]



DBWC12T



DBWC12T Back



DBWC12T Side



DBWC12T Bottom



### [SPECIFICATIONS]

Product Code	Poles	Dimensions HxWxD (mm)	No. of Neutral Links	Conduit Entries	IP Rating
DBWC5T	5	130 x 120 x 90	2 x 5 Hole	10 x ø20.5 - ø29	IP65
DBWC8T	8	195 x 195 x 90	2 x 5 Hole	10 x ø20.5 - ø29 - ø37.5	IP65
DBWC12T	12	190 x 245 x 105	2 x 9 Hole	12 x ø20.5 - ø29 - ø37.5	IP65
DBWC18T	18	200 x 355 x 110	2 x 15 Hole	12 x ø20.5 - ø29 - ø37.5	IP65
DBWC24T	24	360 x 270 x 110	4 x 9 Hole	14 x ø20.5 - ø29 - ø37.5	IP65

### [WARRANTY]

Connected Switchgear weatherproof enclosures come with a trusted 5 Year In House Warranty. That means that you have peace of mind knowing that if a fault develops within a five year period, Connected Group Australia will cover the cost of replacing the product and it's installation.\*

\* See our website for full terms and conditions www.connectedswitchgear.com.au